

METHANE FROM FLARING TOOLKIT



Composition: Measure Density and Infer Gas Composition

Uncategorized > Composition: Measure Density and Infer Gas Composition

Summary

To allow the combustion and destruction efficiencies of a flare system to be estimated, the molecular weight of the flare gas can be helpful. This is normally derived from the composition of the flare gas.

If taking a sample for laboratory analysis or on-line compositional analysis is not possible, then, if the density of the gas that will be routed to flare is known along with its pressure and temperature, the molecular weight can be calculated. In very limited circumstances this molecular weight enables the composition mixture of the flare gas

to be estimated.

How it Works

Using the ideal gas law, we know that at low pressures the density of a gas is directly proportional to its molecular weight as follows:

$$(1) P * M_A = d * RT$$

Where:

P = *absolute pressure*

M_A = *molecular weight of gas*

R = *gas constant*

d = *density of gas*

T = *absolute temperature*

Equation (1) is valid for a single component of gas, to derive for a two gas mixture, we require the following calculation:

$$(2) d = \frac{m}{v}$$

Where:

m = *mass of gas*

v = *volume of gas*

d = *density of gas*

The density of a mixture of two gases A and B could be obtained from the total mass of the gases as follows:

$$(3) \ d = \frac{m_A + m_B}{V} = \frac{m_A}{V} + \frac{m_B}{V}$$

Taking this further we know in the ideal gas law we have the following:

$$(4) \ \frac{m_A}{V} = \frac{P_A * M_A}{RT}$$

This will then give us:

$$(5) \ d = \frac{P_A * M_A}{RT} + \frac{P_B * M_B}{RT}$$

Which we can then simplify to:

$$(6) \ \frac{d * R * T}{P} = X_A * M_A + X_B * M_B$$

Where:

$X = \text{gas mol fraction}$

If we have a gas that has only two components A and B

$$(7) X_A + X_B = 1$$

Then (6) can be simplified to:

$$(8) X_A = \frac{(R \cdot T \cdot d) / P - M_B}{M_A - M_B}$$

From equation (8) using the measured density of the flare gas, we can derive the components of the composition of the flare gas providing we know which two components it is likely to contain.

Equation (8) can then be entered into either the flare meter controller/flow computer or within the DCS / ICSS to derive the composition of the gas, the corresponding molecular weight which will enable the calculation of the combustion and destruction efficiency.

Utilisation of the inference of composition from measured density is not a common application, but can be used when no sampling or analysis facilities are available on the flare systems.

Advantages

- ✓ No Equipment costs
- ✓ Minimal Maintenance costs
- ✓ On-line continuous calculation

Limitations

- ✗ Only applicable for flare gas containing no more than two known compounds
- ✗ Low Accuracy
- ✗ High Uncertainty

Go Deeper

-

Case study

No case study available at this time.

Do I know the gas composition?



Composition: Spectrometry (GC – MS)




Composition: On-Line



Composition: Laboratory Analysis



Composition: Specific Gravity Analyser (Relative Density)



Composition: Wobbe Index Analyser (Calorimeter)